## US005087910A

# United States Patent [19]

## **Guyot-Sionnest**

Patent Number: [11]

5,087,910

Date of Patent:

Feb. 11, 1992

[54] ELECTRONIC KEYBOARD FOR ONE-HAND **OPERATION** 

Laurent Guyot-Sionnest, 82 rue du [76] Inventor:

Général Leclerc, 92270 Bois-Colombes, France

[21] Appl. No.: 585,012

[22] Filed: Sep. 14, 1990

#### Related U.S. Application Data

Continuation of Ser. No. 285,357, Dec. 24, 1988, aban-[63] doned, which is a continuation of Ser. No. 890,464, Jul. 29, 1986, abandoned.

[30]	Foreign	Application	Priority Data
------	---------	-------------	---------------

[51]	Int. Cl. <sup>5</sup>	G09G 3/02
[52]	U.S. Cl	340/711; 341/22;
		400/489
[58]	Field of Search	340/711, 712, 706;
	341/22, 21, 23, 25, 26, 24;	400/484, 473, 402,
	485	486 487 488 489

Jul. 29, 1985 [FR] France ....... 85 11532

#### [56] References Cited

### U.S. PATENT DOCUMENTS

	1/1965 3/1987 1/1977	Seibel et al	340/711 382/13 340/365 R
<b>4,420,744 4,443,789</b>	12/1983 4/1984	Jesson Endfield et al Volnak	341/25 340/365 R

#### FOREIGN PATENT DOCUMENTS

0002247 6/1979 European Pat. Off. .

2360427 3/1978 France.

2418493	9/1979	France .
2064187	6/1981	United Kingdom 400/484
2071578	9/1981	United Kingdom .
2076743	12/1981	United Kingdom .
2149946	6/1985	United Kingdom .

#### OTHER PUBLICATIONS

"Owerty is Obsolete", Interface Age, Circle Inquiry No.

32, Jan. 1978, by Sid Own, pp. 56-59. "Semi-Captive Keyboard", Xerox Disclosure Journal, vol. 1, No. 2, Feb. 1976, by D. C. Kowalski, p. 85. W. C. McCormack, "Single Keybutton Four-Way Switch", IBM Technical Disclosure, vol. 21, No. 8, Jan. 1979, p. 3261.

"Keyboard for Handheld Computer", IBM Technical Disclosure, vol. 27, No. 10A, Mar. 1985.

Primary Examiner-Alvin E. Oberley Assistant Examiner-Xiao M. Wu Attorney, Agent, or Firm-Young & Thompson

#### **ABSTRACT**

The electronic keyboard for one-hand operation, more particularly for generating alphanumeric and analog characters and/or processing instructions, comprises a plurality of keys (2, 4) and an electronic circuit connected electrically to said keys in order to interpret the state of the keys (2, 4) and deliver a signal indicative thereof, said electronic circuit also being connected to a display (6) and to external connection. It comprises at least two keys (2) associated with the fingers of a hand other than the thumb and a key (4) associated with the thumb, each key (2) associated with a finger of the hand other than the thumb being adapted to assume three different states in response to said finger and the thumb key (4) can assume five different states in response to the thumb (see FIG. 1).

### 20 Claims, 7 Drawing Sheets

